

WAAS CH 86537 W11A	APP CRS 116°	Rwy Ldg TDZE Apt Elev	6501 718 722
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 11
COLES COUNTY MEML (MTO)

RNP APCH.

A When local altimeter setting not received, use Champaign/Urbana altimeter setting and increase all DA 82 feet, increase all MDA 100 feet, and increase LPV all Cats visibility $\frac{1}{8}$ mile, LNAV/VNAV all Cats visibility $\frac{3}{8}$ mile, LNAV Cats C and D and Circling Cat C visibility $\frac{1}{4}$ mile, and Circling D visibility $\frac{1}{2}$ mile. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Baro-VNAV and VDP NA when using Champaign/Urbana altimeter setting. Circling NA to Rwy 18 and 36.

MISSED APPROACH:
Climb to 1200 then
climbing left turn to
3000 direct NIBIE
and hold.

ASOS 118.475	CHAMPAIGN APP CON ★ 132.85 290.225	UNICOM 122.7 (CTAF) 0
------------------------	--	---------------------------------



4 NM Holding Pattern

VGS and RNAV glidepath not coincident (VGS Angle 3.00/TCH 26).

WUBTA

YAYSU

ZOSIB 2.9 NM to RW11

*1.1 NM to RW11

RW11

3000

296°

116°

116°

2400

2400

1680*

GP 3.00° TCH 45

6 NM

2.3 NM

1.8 NM

1.1 NM

* LNAV only.

CATEGORY	A	B	C	D
LPV DA	918- $\frac{3}{4}$ 200 (200- $\frac{3}{4}$)			
LNAV/VNAV DA	1175-1 $\frac{5}{8}$ 457 (500-1 $\frac{5}{8}$)			
LNAV MDA	1120-1 402 (400-1)		1120-1 $\frac{1}{8}$ 402 (400-1 $\frac{1}{8}$)	
CIRCLING	1160-1 438 (500-1)	1180-1 458 (500-1)	1240-1 $\frac{1}{2}$ 518 (600-1 $\frac{1}{2}$)	1380-2 658 (700-2)

MIRL Rwy 6-24

HILL Rwy 11-29

REIL Rwy 6, 11, and 24