



LOC/DME I-LEr	APP CRS	Rwy Ldg	7100
109.7	340°	TDZE	1232
Chan 34		Apt Elev	1232

ILS or LOC RWY 34
BRainerd LAKES RGNL (BRD)

RNP APCH - GPS. From GOLLF.	MALSR	MISSED APPROACH: Climb to 1700 then climbing right turn to 4000 direct LAREW LOM and hold, continue climb-in-hold to 4000.
DME required. ADF required.		
VDP NA when using AIT altimeter setting. When local altimeter setting not received, use AIT altimeter setting and increase S-ILS 34 DA to 1484 feet; increase all MDAs 60 feet and S-LOC 34 visibility Cat C/D ¼ SM, and Circling visibility Cat D ¼ SM.		

ASOS 126.775	MINNEAPOLIS CENTER 118.05 239.0	UNICOM 122.7 (CTAF) 0
-----------------	------------------------------------	--------------------------



1700	4000	LAREW	ZIBEG I-LEr 6.7	IRIYA I-LEr 15	One Minute Holding Pattern
		UXOWO I-LEr 3	3000	160° → 6000	
		I-LEr 1.3	I-LEr 2.4	← 340° 4000	
		1.1 NM	0.6	3.7 NM	8.2 NM
CATEGORY	A	B	C	D	
S-ILS 34	1432-½	200 (200-½)			
S-LOC 34	1620-½	388 (400-½)	1620-⅝	388 (400-⅝)	
CIRCLING	1760-1	528 (600-1)	1760-1½	1860-2	
			528 (600-1½)	628 (700-2)	