

RNP APCH - GPS

⚠

Inop table does not apply to LPV all Cats. For inop ALS, increase LNAV/VNAV all Cats visibility to 1 1/8 SM. Circling NA for Cat D southwest of Rwy 13-31.

⚠

When local altimeter setting not received, use DLF altimeter setting: increase LPV DA to 1282 feet; increase LNAV/VNAV DA to 1431 feet; increase all MDAs 40 feet and LNAV visibility Cats C/D 1/8 SM and Circling visibility Cats C/D 1/4 SM.

W

Baro-VNAV NA when using DLF altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17° C or above 54°C.

MALS

⦿

4

≡

≡

MISSED APPROACH: Climb to 4000 direct AREXE and on 069° track to DLF VORTAC and hold, continue climb-in-hold to 4000.

|                        |                                         |                          |                                        |
|------------------------|-----------------------------------------|--------------------------|----------------------------------------|
| ASOS<br><b>118.525</b> | DEL RIO APP CON ★<br><b>119.6 259.1</b> | CLNC DEL<br><b>120.5</b> | UNICOM<br><b>122.8 (CTAF)</b> <b>①</b> |
|------------------------|-----------------------------------------|--------------------------|----------------------------------------|

|           |          |           |
|-----------|----------|-----------|
| ELEV 1002 | <b>D</b> | TDZE 1002 |
|-----------|----------|-----------|

|                           |                    |                        |                            |                            |      |
|---------------------------|--------------------|------------------------|----------------------------|----------------------------|------|
| 4 NM Holding Pattern      |                    | 4000                   | AREXE                      | tr 069°                    | DLF  |
| GP 3.00° TCH 48           |                    | JERUL                  | RORKY                      | HIBUD 1.9 NM to RW13       | RW13 |
| 4000 ← 312° → 132° → 2700 |                    | 2700                   | 1640                       |                            |      |
| 8.6 NM                    |                    | 3.2 NM                 | 1.9                        |                            |      |
| CATEGORY                  | A                  | B                      | C                          | D                          |      |
| LPV DA                    |                    | 1252-3/4               | 250 (300-3/4)              |                            |      |
| LNAV/VNAV DA              |                    | 1401-1                 | 399 (400-1)                |                            |      |
| LNAV MDA                  |                    | 1500-3/4 498 (500-3/4) | 1500-1 1/8 498 (500-1 1/8) |                            |      |
| CIRCLING                  | 1500-1 498 (500-1) | 1560-1 558 (600-1)     | 1740-2 738 (800-2)         | 1740-2 1/4 738 (800-2 1/4) |      |

DEL RIO, TEXAS

Amdt 2C 03SEP26

29°22'N-100°56'W

DEL RIO INTL (DRT)

**RNAV (GPS) RWY 13**