


WAAS CH 86723 W18A	APP CRS 188°	Rwy Ldg TDZE Apt Elev	5000 285 285
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 18

WEEDON FLD (EUF')

RNP APCH - GPS.			MISSED APPROACH: Climb to 1300 then climbing right turn to 2200 direct EPICU and hold.
When local altimeter setting not received, use Columbus, GA altimeter setting and increase LPV DA to 632 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 739 feet and all visibilities ½ SM; increase all MDAs 40 feet and LNAV visibility Cats C and D ½ SM and Circling visibility Cats C and D ¼ SM. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using Columbus, GA altimeter setting.			
ASOS 128.325	ATLANTA APP CON ★ 125.5 323.1	CLNC DEL 134.25 339.8	UNICOM 122.8 (CTAF) 0



ELEV 285		TDZE 285	
188°		81	
5000 X 100		36	
MRL Rwy 18-36		1	
1300		2200	
EPICU		VGS and RNAV glidepath not coincident (VGS Angle 3.00/TCH 26).	
4 NM		Holding Pattern	
2 NM to RW18		CASDO	
RW18		2000	
2 NM		3.3 NM	
7 NM		GP 3.00°	
TCH 40		2200	
008°		188°	
CATEGORY		A	
LPV DA		599-1	
LNAV/VNAV DA		706-1¼	
LNAV MDA		940-1 655 (700-1)	
CIRCLING		1060-2¼	
		775 (800-2¼)	