




LOC I-GLR 111.1	APP CRS 096°	Rwy Ldg 6579 TDZE 1321 Apt Elev 1328
---------------------------	------------------------	---

ILS or LOC RWY 9
GAYLORD RGNL (GLR)

ADF required. RADAR required for procedure entry.		MALSR 	MISSED APPROACH: Climb to 3000 then left turn direct BANGU LOM and hold.
T NA Circling Rwy 18, 36 NA at night. When local altimeter setting not received, use GOV altimeter setting and increase S-ILS 9 DA to 1591 feet; increase all MDAs 80 feet and S-LOC 9 visibility Cat C and D ¾ SM, and Circling visibility Cat C and D ¼ SM. For inop ALS when using GOV altimeter setting, increase S-ILS 9 all Cats visibility to ¾ SM and S-LOC 9 Cats C and D visibility to 1 ¼ SM. For inop ALS, increase S-LOC 9 Cats C and D visibility ¾ SM.			
ASOS 118.375	MINNEAPOLIS CENTER 134.6 354.05		UNICOM 122.8 (CTAF) 



CATEGORY	A	B	C	D
S-ILS 9		1521-1/2	200 (200-1/2)	
S-LOC 9	1860-1/2	539 (600-1/2)	1860-1	539 (600-1)
CIRCLING	1860-1 532 (600-1)	1940-1 612 (700-1)	2040-2 712 (800-2)	2040-2 1/4 712 (800-2 1/4)



EC-1, 03 SEP 2026 to 01 OCT 2026

EC-1, 03 SEP 2026 to 01 OCT 2026