

WAAS CH 69423 W28A	APP CRS 284°	Rwy Ldg TDZE 1189 Apt Elev 1191
--	------------------------	---

RNAV (GPS) RWY 28

KNOX COUNTY (4I3)

RNP APCH.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.

MISSED APPROACH: Climb to 3000 direct BONIF and hold.

AWOS-3PT 126.05	COLUMBUS APP CON 125.95 317.775	CLNC DEL 119.45	UNICOM 123.05 (CTAF) 0
---------------------------	---	---------------------------	---

MISSED APCH FIX

BONIF

4 NM

MSA RW 28 25 NM

3100

Procedure NA for arrival on APE VORTAC airway radials 055 CW 168.

APPLETON APE 3000 099° (13.5)

ELEV 1191

TDZE 1189

10

28

284°

3000

BONIF

*LNAV only

SLAPT 1.7 NM to RW28

WEBUB 2700

PATIE

4 NM Holding Pattern

104°

284°

6000

2800

GP 3.00° TCH 40°

CATEGORY	A	B	C	D
LPV DA		1389-1	200 (200-1)	
LNAV/VNAV DA		1439-1	250 (300-1)	
LNAV MDA		1540-1	351 (400-1)	

MIRL Rwy 10-28 **0**

REIL Rwy 10 and 28 **0**