ILS or LOC RWY 27

PORTER COUNTY RGNL (VPZ)

LOC I-VPZ	APP CRS	Rwy Ldg	6500
109.7	272°	TDZE	770
		Apt Elev	770

ADF required.

T A For inop ALS, increase S-LOC 27 Cats C and D visibility to 1 SM.

MALSR

MISSED APPROACH: Climb to 1400, then climbing right turn to 2600 direct SEDLY LOM and hold, continue climb-in-hold to 2600.

ASOS	SOUTH BEND APP CON ★	UNICOM
125.875	132.05 257.8	122.725 (CTAF) L

Procedure NA for arrivals at CGT VORTAC on V8-92 westbound.



ELEV 770 D TDZE 770





HIRL Rwy 9-27 L
MIRL Rwy 18-36 L
REIL Rwys 9, 18 and 36 L

FAF to MAP 5.3 NM

Knots	60	90	120	150	180
Min:Sec	5:18	3:32	2:39	2:07	1:46

CATEGORY	A	B	C	D
S-ILS 27	970-½ 200 (200-½)			
S-LOC 27	1120-½ 350 (400-½)		1120-⅝ 350 (400-⅝)	
CIRCLING	1260-1 490 (500-1)	1300-1 530 (600-1)	1360-1½ 590 (600-1½)	1620-2¾ 850 (900-2¾)

EC-2, 03 SEP 2026 to 01 OCT 2026
EC-2, 03 SEP 2026 to 01 OCT 2026