

APP CRS
246°

Rwy Ldg
TDZE
Apt Elev

3204
2098
2099

RNAV (GPS) RWY 25

EBENSBURG (9G8)

▼

▲ NA

Procedure NA at night. Rwy 25 helicopter visibility reduction below 1 SM NA. Obtain local altimeter setting on CTAF; when not received, use Johnstown altimeter setting and increase all MDA 60 feet and visibility Cat C ¼ SM.

MISSED APPROACH: Climbing right turn to 4100 direct EXPYR and hold.

JOHNSTOWN APP CON ★ 121.2 299.2	UNICOM 122.8 (CTAF) 0
------------------------------------	--------------------------

1636 X 150
1.9% UP

3204 X 50
0.6% UP

246°

4100 EXPYR

Visual Segment - Obstacles.

5 NM Holding Pattern

RW25

FAND A 1.8 NM to RW25

DEZZZ

3900

2720

1.8 NM

3.6 NM

6.1 NM

CATEGORY	A	B	C	D
LNAV MDA	2620-1	522 (600-1)	2620-1½ 522 (600-1½)	NA

MIRL Rwy 7-25 0

EBENSBURG (9G8)

EBENSBURG, PENNSYLVANIA

Orig-F 30NOV23

40°28'N-78°47'W

RNAV (GPS) RWY 25