

VORTAC RMG	APP CRS	Rwy Idg	N/A
115.4	187°	TDZE	N/A
Chan 101		Apt Elev	974

VOR-A

POLK COUNTY/CORNELIUS MOORE FLD (4A4)



▼

NA

Obtain local altimeter setting on CTAF; when not received, use Cartersville altimeter setting and increase all MDAs 80 feet, and visibility Cat C/D ¼ SM, ACPAJ fix minimums visibility Cat C/D ¼ SM.

MISSED APPROACH: Climbing right turn to 3500 direct RMG VORTAC and hold, continue climb in hold to 3500.

ATLANTA CENTER 124.5 270.325	UNICOM 122.8 (CTAF) ①
--	---------------------------------



Procedure NA on V235 westbound without holding at FELTO. ATC clearance required.			
3500	RMG	*1740 when using Cartersville altimeter setting.	One Minute Holding Pattern
ACPAJ RMG 7.5			
MAFIF RMG 8.7			
1660*			
1.2 NM 7.5 NM			
CATEGORY	A	B	C
CIRCLING	1660-1	686 (700-1)	1660-2 686 (700-2)
ACPAJ FIX MINIMUMS (DME REQUIRED)			
CIRCLING	1520-1	546 (600-1)	1520-1½ 546 (600-1½)