

LOC/DME I-FGH
109.35
Chan **30** (Y)

APP CRS
041°

Rwy Ldg **4775**
TDZE **58**
Apt Elev **72**

EASTON/NEWNAM FLD (ESN)
ILS or LOC RWY 4

RADAR and DME required for procedure entry. DME required for LOC only.

▼

▲

Circling Rwy 15, 33 NA at night. Autopilot coupled approach NA below 1000.


MISSED APPROACH: Climb to 2000 on heading 041° and on ATR VOR/DME R-283 to ORETE INT/ATR 31.6 DME and hold.

ATIS
124.475

POTOMAC APP CON
133.75 254.35

EASTON TOWER ★
118.525 (CTAF) **0**

GND CON
119.075



One Minute Holding Pattern

GS unusable below 600.

2000

ATR R-283

ORETE

4600

2000

GS 3.00° TCH 44

221°

041°

041°

1600

1600

3.4 NM

1.4 NM

6 NM

WEGRO I-FGH 5.8

RIKME I-FGH 11.8

1600

2.5

1

*LOC only

CATEGORY	A	B	C	D
S-ILS 4		600-1 ⁵ / ₈	542 (600-1 ⁵ / ₈)	
S-LOC 4	540-1	482 (500-1)	540-1 ³ / ₈	482 (500-1 ³ / ₈)
CIRCLING	540-1 468 (500-1)	640-1 568 (600-1)	640-1 ¹ / ₂ 568 (600-1 ¹ / ₂)	740-2 ¹ / ₄ 668 (700-2 ¹ / ₄)

ELEV 72

D

TDZE 58

TWR

5300 X 100

4000 X 100

0.5% UP

0.7% UP

041°

HIRL Rwy 4-22 **0**

REIL Rws 15, 22 and 33 **0**

MIRL Rws 15-33 **0**