



WAAS CH 56631 W33A	APP CRS 330°	Rwy Ldg TDZE 1011 Apt Elev 1011
--	------------------------	---

RNAV (GPS) RWY 33

NEW ULM MUNI (ULM)

RNP APCH. Circling NA to Rwy 4 and 22. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM, LNAV Cat D to 1 ½ SM.	MALSF 	MISSED APPROACH: Climb to 3000 direct KADPE and hold.
---	-----------	---

AWOS-3 118.325	MINNEAPOLIS CENTER 127.1 290.2	GCO 121.725	UNICOM 123.0 (CTAF) 0
--------------------------	--	-----------------------	---------------------------------



3000	KADPE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).			
*LNAV only.	ZUDIL 2.5 NM to RW33	CETOT 2500	YEBUY	4 NM Holding Pattern	
	1.1 NM to RW33	1840	330°	150°	6000/3000
		2500	330°	330°	
					GP 3.00° TCH 40
CATEGORY	A	B	C	D	
LPV DA	1211-¾	200 (200-¾)			
LNAV/VNAV DA	1312-¾	301 (400-¾)			
LNAV MDA	1400-¾ 389 (400-¾)	1400-7/8 389 (400-7/8)			
CIRCLING	1440-1 429 (500-1)	1500-1 489 (500-1)	1620-1¾ 609 (700-1¾)	1620-2 609 (700-2)	