


WAAS CH 86229 W18A	APP CRS 179°	Rwy Idg TDZE Apt Elev	5849 71 75
--	------------------------	-----------------------------	---------------------------------------

RNAV (GPS) RWY 18
ST LANDRY PARISH (OPL)

NA Bara-VNAV NA when using Lafayette altimeter setting. For uncompensated Bara-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 43°C (109°F). When VGSi inop, Straight-in/Circling Rwy 18 procedure NA at night. DME/DME RNP-0.3 NA. Helicopter visibility reduction below 1 SM NA. Circling to Rwy 6/24 NA at night. When local altimeter setting not received, use Lafayette altimeter setting: increase LPV DA to 377 feet, LNAV/VNAV DA to 442 feet, and visibility LNAV/VNAV all Cats ¼ SM; increase all MDA 60 feet and visibility LNAV Cat C and D and Circling Cat C and D ¼ SM.

MISSED APPROACH: Climb to 2300 direct YOLUG and hold.

AWOS-3PT 118.775	LAFAYETTE APP CON ★ 128.7 268.7	UNICOM 123.0 (CTAF) L
----------------------------	---	--



MISSED APCH FIX

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 58).

2300 YOLUG

2000 ← 359° 179° →

JUGBO

HUIG 1800

ZOXEB 1.5 NM to RW18

*RNAV only.

1800


GP 3.00° TCH 52

*600

6.8 NM 3.8 NM 1.5 NM

RW18

CATEGORY	A	B	C	D
LPV DA	321-1 250 (300-1)			
RNAV/VNAV DA	386-1 315 (400-1)			
RNAV MDA	480-1 409 (500-1)		480-1½ 409 (500-1½)	
CIRCLING	780-1 705 (800-1)		780-2 705 (800-2)	920-2¾ 845 (900-2¾)



RNAV (GPS) RWY 18

SC-4, 03 SEP 2026 to 01 OCT 2026