RNAV (GPS) RWY 17

CLINTON RGNL (CLK)

WAAS	APP CRS	Rwy Ldg	4305
CH 93922	172°	TDZE	1616
W17A		Apt Elev	1616

T A DME/DME RNP-0.3 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -12°C (11°F) or above 54°C (130°F). Circling NA to Rwy 13 and 31. When local altimeter setting not received, use Weatherford altimeter setting: Increase DA to 1898 and all visibilities ⅛ mile; increase all MDA 40 feet and visibility Cat C ¼ mile. Baro-VNAV and VDP NA when using Weatherford altimiter setting.

MISSED APPROACH: Climb to 4000 direct OSUCU and hold.

AWOS-3	FORT WORTH CENTER	UNICOM
119.225	128.4 269.37	122.8 (CTAF) L



CATEGORY	A	B	C	D
LPV DA	1866-⅞	250 (300-⅞)		NA
LNAV/VNAV DA	1866-⅞	250 (300-⅞)		NA
LNAV MDA	1980-1	364 (400-1)		NA
CIRCLING	2100-1 484 (500-1)	2220-1 604 (700-1)	2320-2 704 (800-2)	NA

MIRL Rwy 17-35 L
REIL Rwys 17 and 35 L

SC-1, 03 SEP 2026 to 01 OCT 2026
SC-1, 03 SEP 2026 to 01 OCT 2026