

WAAS CH 49210 W14A	APP CRS 138°	Rwy Ldg TDZE 1039 Apt Elev 1039
--	------------------------	---

RNAV (GPS) RWY 14

BENSON MUNI (BBB)

RNP APCH - GPS.



▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro-VNAV and VDP NA when using Appleton altimeter setting. When local altimeter setting not received, use Appleton altimeter setting and increase LPV DA to 1422 feet and all visibilities 1/8 SM; increase LNAV/VNAV DA to 1466 feet and all visibilities 1/8 SM; increase all MDAs 40 feet.

MISSED APPROACH: Climb to 2700 direct FETUD and hold.

AWOS-3PT 118.45	MINNEAPOLIS CENTER 125.5 323.1	UNICOM 122.8 (CTAF) 0
---------------------------	--	---------------------------------



DOSCA		CUKUP		2700	FETUD
4 NM Holding Pattern		2700		1.4 NM to RWY 14	RWY 14
6000 ← 318°		138° →		2700	
2700		138°		2700	
GP 3.00°		TCH 40			
		6 NM		3.6 NM	
				1.4	
CATEGORY	A	B		C	D
LPV DA	1382-1	343 (400-1)		NA	
LNAV/VNAV DA	1426-1 1/8	387 (400-1 1/8)		NA	
LNAV MDA	1540-1	501 (600-1)		NA	

NC-1, 03 SEP 2026 to 01 OCT 2026

NC-1, 03 SEP 2026 to 01 OCT 2026