

WAAS CH 61234 W23A	APP CRS 232°	Rwy Ldg TDZE 1523 Apt Elev 1545
--	------------------------	---

RNAV (GPS) RWY 23

SCOTT MUNI (SCX)

▼

▲NA

Night landing: Rwy 5 NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Monticello altimeter setting: increase LPV all Cats DA to 2005 feet, LNAV/VNAV all Cats DA to 2153 feet, LPV visibility ½ mile, LNAV/VNAV ⅔ mile; increase all MDA 240 feet and LNAV Cat C/D visibility ⅔ mile, Circling Cat B ¼ mile, Circling Cat C 1 mile and Circling Cat D ¾ mile. Inop table does not apply to LPV and LNAV all Cats. For inop ODALS, increase LNAV/VNAV Cat D visibility to 1 ⅓ mile. For inop ODALS when using Monticello altimeter setting, increase LPV all Cats visibility to 1½ mile, LNAV/VNAV all Cats to 2 ½ mile. When using Monticello altimeter setting, inop table does not apply to LNAV Cats A/C/D. VDP and Baro-VNAV NA when using Monticello altimeter setting.

ODALS

MISSED APPROACH:
Climb to 3900 direct
ZITGO and hold.

AWOS-3 135.025	INDIANAPOLIS CENTER 124.625 371.925	UNICOM 122.8 (CTAF)
--------------------------	---	-------------------------------

30 NM to COPEP (Inop)

5 NM

052° 232°

(IF/IAF) COPEP

3700 232° (6)

(FAF) GATGE

1784

LUKYE 3 NM to RWY 23

RWY 23

30 NM to COPEP

142° 8 NM 4800 322°

COPEP

4800 6100

MISSED APCH FIX

ZITGO

051° 231°

4 NM

3900

ZITGO

*LNAV only.

1.5 NM to RWY 23

1.5 NM to RWY 23

3.7 NM

6 NM

5 NM Holding Pattern

052° 232°

4800

GP 3.00° TCH 52

*2500

3700

3700

LUKYE 3 NM to RWY 23

GATGE

COPEP

CATEGORY	A	B	C	D
LPV DA		1773-1	250 (300-1)	
LNAV/DA VNAV		1921-1 ⅓	398 (400-1 ⅓)	
LNAV MDA	2040-1	517 (500-1)	2040-1 ⅓	517 (500-1 ⅓)
CIRCLING	2040-1	495 (500-1)	2200-1 ¾	2260-2 ¼
			655 (700-1 ¾)	715 (800-2 ¼)

MRL Rwy 5-23

REIL Rws 5 and 23

ONEIDA, TENNESSEE

SCOTT MUNI (SCX)

Amdt 1B 04FEB16

36°27'N-84°35'W

RNAV (GPS) RWY 23