

LOC/DME I-RLD 110.5 Chan 42	APP CRS 189°	Rwy Ldg TDZE Apt Elev	4009 390 394
---	------------------------	-----------------------------	---


LOC RWY 19
RICHLAND (RLD)

NA VDP NA when using PSC altimeter setting. For inop ALS, increase S-19 Cats C and D visibility to 3 SM. When local altimeter setting not received, use PSC altimeter setting and increase all MDAs 20 feet and increase HOTUX fix minimums S-LOC 19 visibility Cat C/D $\frac{1}{2}$ SM, and Circling visibility Cat C $\frac{1}{2}$ SM. HOTUX fix minimum: For inop ALS, increase S-19 Cats C and D visibility to $\frac{1}{2}$ SM.


MALS

MISSED APPROACH: Climbing right turn to 4000 on heading 045° and on PSC VOR/DME R-337 to BAKCA INT/I-RLD 13.7 DME and hold, continue climb-in-hold to 4000.

AWOS-3PT 132.675	SPOKANE APP CON★ 128.75 377.2	CLNC DEL 122.4	UNICOM 122.7 (CTAF) 0
----------------------------	---	--------------------------	--



ELEV 394	TDZE 390
----------	----------



REIL Rwy 1 and 19 L

MIRL Rwy 1-19 and 8-26

FAF to MAP 5 NM

Knots	60	90	120	150	180
Min:Sec	5:00	3:20	2:30	2:00	1:40

RICHLAND, WASHINGTON

Amdt 10 07AUG25

4000
hdg 045°

PSC R-337

BAKCA
△

VGSI and descent angles not coincident
(VGSI Angle 3.00/TCH 30).

FIXOV INT
I-RLD 6

BAKCA
I-RLD 13.7

One Minute Holding Pattern

HOTUX INT
I-RLD 3.7

JUDUB
I-RLD 1

I-RLD 2.2

3.00°
TCH 40

189°

009°

4000

1360

2100

0.3 NM 1.2 NM 1.5 NM 2.3 NM 7.7 NM

CATEGORY	A	B	C	D
S-19	1360-1 970 (1000-1)	1360-1¼ 970 (1000-¼)	1360-2½	970 (1000-2½)
CIRCLING	1360-1¼ 966 (1000-¼)	1360-1½ 966 (1000-½)	1360-3 966 (1000-3)	1960-3 1566 (1600-3)
HOTUX FIX MINIMUMS (DUAL VOR RECEIVERS OR DME REQUIRED)				
S-19	880-7/8	490 (500-7/8)	880-1½	490 (500-1½)
CIRCLING	880-1 486 (500-1)	1000-1 606 (700-1)	1200-2¼ 806 (900-2¼)	1960-3 1566 (1600-3)

RICHLAND (RLD)

LOC RWY 19

46°18'N-119°18'W

NW-1, 03 SEP 2026 to 01 OCT 2026

NW-1, 03 SEP 2026 to 01 OCT 2026