

APP CRS
322°

Rwy Ldg
4209

TDZE
1313

Apt Elev
1321

RNAV (GPS) RWY 32
STEPHENVILLE CLARK RGNL (SEP)

▼

▲

DME/DME RNP-0.3 NA. Rwy 32 helicopter visibility reduction below 1 SM NA. Straight-in Rwy 32 NA at night, circling Rwy 32 NA at night.

MISSED APPROACH: Climb to 3600 direct WOGAN and hold.

AWOS-3PT 118.075	FORT WORTH CENTER 135.375 354.05	UNICOM 122.8 (CTAF)
---------------------	-------------------------------------	------------------------

The main chart illustrates the RNAV (GPS) RWY 32 approach. Key features include:

- WOGAN**: 4 NM from the start, 142° bearing, 322° heading.
- WOGAN Holding**: 30 NM to COVON, 142° bearing, 232° heading, 3600 ft altitude.
- WOGAN to RWY 32**: 1536 ft altitude, 322° heading.
- CUGOR**: (FAF) waypoint, 3000 ft altitude, 322° heading.
- HOVIR**: (IF/IAF) waypoint, 3600 NoPT, 232° heading, 322° heading.
- HOVIR Holding**: 30 NM to HOVIR (NoPT), 232° heading, 3600 ft altitude.
- WINIT**: (IAF) waypoint, 3600 NoPT, 052° heading, 322° heading.
- WOGAN to WINIT**: 30 NM, 142° bearing, 052° heading, 3600 ft altitude.

ELEV 1321	TDZE 1313			
3600 WOGAN CUGOR HOVIR 4 NM Holding Pattern 142° → 3600 ← 322° 3000 3.04° TCH 40 5.2 NM 6 NM				
CATEGORY	A	B	C	D
LNAV MDA	1820-1	507 (500-1)	1820-1½	507 (500-1½)
CIRCLING	1820-1	499 (500-1)	2000-2 679 (700-2)	2000-2¼ 679 (700-2¼)

STEPHENVILLE, TEXAS

Orig-B 20MAY21

32°13'N-98°11'W

STEPHENVILLE CLARK RGNL (SEP)
RNAV (GPS) RWY 32