


WAAS CH 63129 W08A	APP CRS 082°	Rwy Ldg 3501 TDZE 739 Apt Elev 741
--	------------------------	---

RNAV (GPS) RWY 8

MACKINAC ISLAND (MCD)

RNP APCH.	MISSED APPROACH: Climb to 2500 direct HUVTI and hold.
▼ ▲ Rwy 8 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Pellston altimeter setting and increase all MDA 60 feet, increase LP and LNAV Cat C visibility ½ SM and Circling Cat C visibility ¼ SM. Straight-in and Circling Rwy 8 NA at night.	

AWOS-3P 118.275	MINNEAPOLIS CENTER 134.6 354.05	UNICOM 122.7 (CTAF)	122.8
---------------------------	---	-------------------------------	--------------



4 NM Holding Pattern	Visual Segment - Obstacles.			2500	HUVTI
	WAKMA	NUBKE	JUIB 1.5 NM to RW08	RW08	
6000 2500	262° 082°	082°	2400	1240	
7.2 NM		3.6 NM	1.5		
CATEGORY	A	B	C	D	
LP MDA	1080-1 341 (400-1)				NA
LNAV MDA	1120-1	381 (400-1)	1120-1½ 381 (400-1½)	NA	
CIRCLING	1320-1	579 (600-1)	1320-1½ 579 (600-1½)	NA	

