

WAAS CH 82041 W10A	APP CRS 096°	Rwy Ldg TDZE 1089 Apt Elev 1090
--	------------------------	---

RNAV (GPS) RWY 10

NEW CASTLE HENRY COUNTY MARLATT FLD (UWL)

RNP APCH - GPS.


▼

⚠

Rwy 10 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Baro-VNAV and VDP NA when using AID altimeter setting. When local altimeter setting not received, use AID altimeter setting and increase LPV DA to 1408 feet; increase LNAV/VNAV DA to 1424 feet; increase all MDAs 80 feet and LNAV visibility Cats C and D $\frac{3}{8}$ SM, and Circling visibility Cats C and D $\frac{1}{2}$ SM.

MISSED APPROACH:
Climb to 3000 direct TASUY and hold.

AWOS-3 132.375	INDIANAPOLIS APP CON 135.45 317.8	UNICOM 123.05 (CTAF) 0
--------------------------	---	----------------------------------



ELEV 1090		TDZE 1089	
4 NM Holding Pattern		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 46).	
GP 3.00° TCH 46		TASUY	
7.6 NM		2.8 NM	
0.8 NM		1.1 NM	
CATEGORY	A	B	C
LPV DA	1339-1	250 (300-1)	
LNAV/VNAV DA	1355-1	266 (300-1)	
LNAV MDA	1460-1	371 (400-1)	
CIRCLING	1520-1 430 (500-1)	1540-1 450 (500-1)	1760-1¾ 670 (700-1¾)
MIRL Rwy 10-28 0		REIL Rwy 10 and 28 0	

EC-2, 03 SEP 2026 to 01 OCT 2026

EC-2, 03 SEP 2026 to 01 OCT 2026