

WAAS CH 77818 W07A	APP CRS 065°	Rwy Idg 5003 TDZE 147 Apt Elev 147
--	------------------------	---

RNAV (GPS) RWY 7

MARLBORO COUNTY JETPORT/H E AVENT FLD (BBP)

RNP APCH.

▼

Baro-VNAV NA when using Florence altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 48°C. Rwy 7 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Florence altimeter setting and increase all DA 61 feet and MDA 80 feet; increase LPV all Cats, LNAV/VNAV all Cats, and LNAV Cats C and Cat D visibility ¼ mile. VDP NA with Florence altimeter setting.

⚠

MISSED APPROACH: Climb to 2500 direct LADKE and hold.

AWOS-3PT 123.825	FLORENCE APP CON ★ 118.6 341.7	UNICOM 122.8 (CTAF)
----------------------------	--	-------------------------------

The main chart displays the RNAV (GPS) RWY 7 approach. Key features include:

- Waypoints:** LONCI, WILSI, DUGVE, SAGPE, and RW07.
- Altitudes:** 2500, 3200, 1900, 1065, 227±, 356, 296±, 432, 640, 512, 564, 763.
- Distances:** 30 NM to WILSI, 30 NM to LONCI (NoPT), 15 NM to SAGPE, 4 NM, 7 NM, 3.9 NM, 1.4 NM.
- Angles:** 155°, 245°, 335°, 065°, 1065°.
- Obstacles:** 564, 432, 640, 512.
- Navigation Aids:** LADKE (4 NM, 066°, 246°).

This section shows the holding pattern and the GP 3.00° TCH 40. Key features include:

- Holding Pattern:** LONCI, 2500, 245°, 065°.
- GP 3.00° TCH 40:** 2500, 245°, 065°.
- Distances:** 7 NM, 3.9 NM, 1.4 NM.
- Angles:** 245°, 065°.
- Obstacles:** 2500, 1900.
- Navigation Aids:** LADKE (2500).

CATEGORY	A	B	C	D
LPV DA	437-1	290 (300-1)		
LNAV/VNAV DA	507-1¼	360 (400-1¼)		
LNAV MDA	620-1	473 (500-1)	620-1¼ 473 (500-1¼)	620-1½ 473 (500-1½)

This section shows the ELEV 147, TDZE 147, and RWY 7. Key features include:

- ELEV 147, TDZE 147:** 147, 147.
- RWY 7:** 5003 x 74, 065°.
- Obstacles:** 5003 x 74.
- Navigation Aids:** LADKE (2500).

BENNETTSVILLE, SOUTH CAROLINA

Amtd 1B 07NOV19

MARLBORO COUNTY JETPORT/H E AVENT FLD (BBP)

34°37'N-79°44'W

RNAV (GPS) RWY 7