

WAAS CH 42607 W36A	APP CRS 004°	Rwy Ldg TDZE 36 Apt Elev 39	5003
--	------------------------	---	-------------

RNAV (GPS) RWY 36

FALSE RIVER RGNL (HZR)

RNP APCH - GPS.


⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. Baro-VNAV and VDP NA when using BTR altimeter setting. When local altimeter setting not received, use BTR altimeter setting: increase LPV DA to 337 feet; increase LNAV/VNAV DA to 463 feet and all visibilities ½ SM; increase all MDAs 60 feet and LNAV visibility Cats C and D ½ SM, and Circling visibility Cat C ¼ SM.

ODALS

MISSED APPROACH:
Climb to 2300 direct FENPU and hold.

AWOS-3PT 121.250	BATON ROUGE APP CON★ 120.3 278.3	UNICOM 122.8 (CTAF) 0
----------------------------	--	---------------------------------



4 NM Holding Pattern		VGSi and RNAV glidepath not coincident (VGSi Angle 3.00/TCH 50).		2300	FENPU
6000 ← 184°		OVB AE		2100	CEBGA
2100 → 004°		2100		2100	2100
GP 3.00°		TCH 50		1.4 NM to RW36	RW36
5.9 NM		5 NM		1.4 NM	
CATEGORY	A	B	C	D	
LPV DA	286-¾		250 (300-¾)		
LNAV/VNAV DA	412-1		376 (400-1)		
LNAV MDA	520-¾	484 (500-¾)	520-1¼	484 (500-1¼)	
CIRCLING	520-1	481 (500-1)	600-1½ 561 (600-1½)	600-2 561 (600-2)	

