

YUMA, ARIZONA

VOR RWY 6

VORTAC BZA
116.8
Chan 115

APCH CRS
048°

Rwy Idg
TDZE 387
Arpt Elev 433

[USA] LAGUNA AAF (YUMA PROVING GROUND) (KLGFB)

RADAR required for holding.

Procedure not authorized at night.

NA ** Circling not authorized NW of rwy 06 and 18.

ATIS
128.225

YUMA APP CON
124.7 371.975

TOWER *
126.2 (CTAF) 242.175

GND CON
121.8 229.4

Helicopter visibility reduction not authorized.

Procedure not authorized when airfield closed.

Unlit road 379' MSL, 314' from threshold.

Obtain local altimeter setting on CTAF.
When not received, use Yuma MCAS Intl altimeter setting.

R-2306E

723

638

599

R-048

R-2307

628

770

1320

048°

CEKDU BZA 5.6

258°

200K

078°

HOLD 3800

IAF

BARD

116.8 BZA

Chan 115

UNITED STATES

MEXICO

One Minute Holding Pattern

BZA VORTAC

Visual Segment - Obstacles

3800

BZA

1400

when using Yuma MCAS Intl altimeter setting

BZA 11.6

5.6 NM

6 NM

MSA BZA 2.5 NM

180°

270°

010°

3700

17,000

4400

2674

ELEV 433

TDZE 387

CATEGORY	A	B	C	D
S-6*	1320-1¼ 933 (900-1¼)	1320-2½ 933 (900-2½)		
CIRCLING**	1320-1¼ 887 (900-1¼)	1320-2¾ 887 (900-2¾)	1320-3 887 (900-3)	
DME MINIMA				
S-6*	1040-1 653 (700-1)	1040-1⅞ 653 (700-1⅞)		
CIRCLING**	1080-1 647 (700-1)	1080-1⅞ 647 (700-1⅞)	1080-2 647 (700-2)	
YUMA MCAS/YUMA Intl ALTIMETER SETTING				
S-6*	1400-1¼ 1013 (1000-1¼)	1400-1½ 1013 (1000-1½)	1400-3 1013 (1000-3)	
CIRCLING**	1400-1¼ 967 (1000-1¼)	1400-1½ 967 (1000-1½)	1400-3 967 (1000-3)	
YUMA MCAS/YUMA Intl ALTIMETER SETTING DME MINIMA				
S-6*	1120-1 733 (700-1)	1120-2 733 (700-2)		
CIRCLING**	1160-1 727 (800-1)	1160-2 727 (800-2)	1160-2¼ 727 (800-2¼)	

81

485

TWR 463

0.8% UP

0.8% UP

6043 x 100

048°

36

501

MIRL Rwy 18-36

FAF to MAP 11.6 NM

Knots	60	90	120	150	180
Min:Sec	11:36	7:44	5:48	4:38	3:52

YUMA, ARIZONA

32° 52'N-114° 24'W

LAGUNA AAF (YUMA PROVING GROUND) (KLGF)

VOR RWY 6

SW-4, 03 SEP 2026 to 01 OCT 2026

SW-4, 03 SEP 2026 to 01 OCT 2026