RNAV (GPS) RWY 7

THE FLORIDA KEYS MARATHON INTL (MTH)

WAAS	APP CRS	Rwy Ldg	5008
CH 99605	071°	TDZE	6
W07A		Apt Elev	7

RNP APCH-GPS.

Rwy 7 helicopter visibility reduction below 1 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 12°C or above 54°C. Baro-VNAV NA when using EYW altimeter setting. Procedure NA at night. When local altimeter setting not received, use EYW altimeter setting: increase LPV DA to 482 feet and all visibilities ¼ SM, LNAV/VNAV DA to 474 feet and all visibilities ⅜ SM, increase all MDAs 100 feet and LNAV Cat C/D visibility ¼ SM and Circling Cat C/D visibility ½ SM.

MISSED APPROACH: Climb to 2000 direct LOGEY and hold.

ASOS	MIAMI CENTER	UNICOM
135.525	133.5 306.9	122.975 (CTAF) L



CATEGORY	A	B	C	D
LPV DA	389-1⅛ 383 (400-1⅛)			
LNAV/VNAV DA	381-1 375 (400-1)			
LNAV MDA	600-1 594 (600-1)		600-1¾ 594 (600-1¾)	
CIRCLING	600-1 593 (600-1)		620-1¾ 613 (700-1¾)	660-2 653 (700-2)

REIL Rwy 7 L
MIRL Rwy 7-25 L

SE-3, 03 SEP 2026 to 01 OCT 2026
SE-3, 03 SEP 2026 to 01 OCT 2026