


WAAS CH 45520 W33A	APP CRS 326°	Rwy Ldg 4000 TDZE 984 Apt Elev 984
--	------------------------	---


RNAV (GPS) RWY 33
BRENNER FLD (FNB)

RNP APCH - GPS.		
T	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. Baro-VNAV NA when using AFK altimeter setting. When local altimeter not received, use AFK altimeter setting and increase LPV DA to 1338 and LNAV/VNAV DA to 1380, increase all MDAs 120 feet.	MISSED APPROACH: Climb to 3000 direct COVUT and hold.

ASOS 119.275	ST JOSEPH APP CON ★ 120.35 360.8	UNICOM 122.8 (CTAF) ①
------------------------	--	---------------------------------



ELEV 984	TDZE 984
MIRL Rwy 15-33 L	
REIL Rwys 15 and 33 L	



3000
↑
COVUT

ZIGNI
1.6 NM to RW33

TAYUG
2700

USACE

4 NM Holding Pattern

146° → 6.00
← 326° 3.00

GP 3.00°
TCH 40

1.6 — 3.7 NM — 6.7 NM

CATEGORY	A	B	C	D
LPV DA	1234-1	250 (300-1)		NA
LNAV/VNAV DA	1276-1	292 (300-1)		NA
LNAV MDA	1380-1	396 (400-1)		NA
CIRCLING	1560-1	576 (600-1)		NA