

WAAS
CH **86428**
W21A

APP CRS
211°

Rwy Ldg
TDZE **470**
Apt Elev **473**

RNAV (GPS) RWY 21

FLORA MUNI (F.O.A.)

RNP APCH.



▼

⚠

Circling NA to Rwy's 15 and 33. Baro-VNAV and VDP NA when using Olney-Noble altimeter setting.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Rwy 21 helicopter visibility reduction below $\frac{3}{4}$ SM NA. When local altimeter setting not received, use Olney-Noble altimeter setting and increase LPV DA to 779 feet, LNAV/VNAV DA to 838 feet and increase LNAV/VNAV visibility all Cats $\frac{1}{8}$ SM, increase all MDA 40 feet.

MISSED APPROACH:
Climb to 2200 direct JISID and hold.

AWOS-3 120.175	KANSAS CITY CENTER 127.7 351.825	UNICOM 122.7 (CTAF) 0
--------------------------	--	---------------------------------



CATEGORY	A	B	C	D
LPV DA	746-1	276 (300-1)		NA
LNAV/VNAV DA	805-1	335 (400-1)		NA
LNAV MDA	920-1	450 (500-1)	920-1 $\frac{3}{8}$ 450 (500-1 $\frac{3}{8}$)	NA
CIRCLING	940-1	467 (500-1)	1160-2 687 (700-2)	NA

