

ATIS
118.35
GND CON
121.7
GOODYEAR TOWER★
120.1 239.3
LUKE DEP CON★
125.45 263.125
PHOENIX DEP CON
120.7 239.0

TAKEOFF OBSTACLE NOTES

Rwy 3: Poles beginning 159′ from DER, 267′ right of centerline, up to 47′ AGL/1015′ MSL.
Building 1512′ from DER, 828′ right of centerline, 48′ AGL/1014′ MSL.
Tree 1957′ from DER, 551′ right of centerline, up to 49′ AGL/1019′ MSL.

Rwy 21: Transmission tower 2610′ from DER, 1078′ left of centerline, 125′ AGL/1047′ MSL.
Transmission tower 3190′ from DER, 311′ left of centerline, 112′ AGL/1031′ MSL.
Pole 3193′ from DER, 308′ left of centerline, 112′ AGL/1030′ MSL.

NOTE: RNAV 1.

NOTE: GPS required.

TAKEOFF MINIMUMS

Rwy 3: Standard with minimum climb of 500′ per NM to 1480 then minimum climb of 431′ per NM to 4600.

Rwy 21: Standard with minimum climb of 500′ per NM to 1480.

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 3: Climb heading 028° to 1480, then right turn direct RUPOY thence. . . .

TAKEOFF RUNWAY 21: Climb heading 208° to 1480, then direct RUPOY thence. . . .

. . . .on track 140° to POTER. Expect filed altitude 3 minutes after departure.

SW-4, 03 SEP 2026 to 01 OCT 2026
SW-4, 03 SEP 2026 to 01 OCT 2026