LOC I-AEG	APP CRS	Rwy Ldg	7398
110.1	215°	TDZE	5817
		Apt Elev	5837

ILS or LOC RWY 22
DOUBLE EAGLE II (AEG)

When local altimeter setting not received, use Albuquerque Intl Sunport altimeter setting and increase all DA 94 feet, increase all MDA 100 feet, and increase visibility S-LOC 22 Cats C/D ¼ mile, Circling Cats C/D ½ mile. For inop MALSR when using Albuquerque Intl Sunport altimeter setting, increase visibility S-ILS 22 all Cats ⅜ mile.

MALSR

MISSED APPROACH: Climb to 6500 then climbing right turn 7700 direct DUDLE LOM and hold.

ATIS	ALBUQUERQUE APP CON	DOUBLE EAGLE II TOWER ★	GND CON
119.025	127.4 253.5	120.15 (CTAF) L	121.625

ADF REQUIRED

AWASH

035°

(CFVLF)

1 min

215°

LOM/IAF DUDLE 351 AE

LOCALIZER 110.1 I-AEG

5886±

8000 9000 7000

ALTERNATE MISSED APCH FIX AWASH 136° 316° 110.6 SAF R-238 Chan 43 113.2 ABQ R-316 Chan 79

7900 013° (11.5)

MSA AE 25 NM 180° 8100 11900 360° 7000

ALBUQUERQUE 113.2 ABQ Chan 79

ELEV 5837 TDZE 5817

215°

TWR

17

0.4% UP

7398 X 100

5983 X 100

35

REIL Rwys 17 and 35 L

MIRL Rwys 4-22 and 17-35 L

FAF to MAP 5.5 NM					
Knots	60	90	120	150	180
Min:Sec	5:30	3:40	2:45	2:12	1:50

6500	7700	AE

AE LOM 7629

One Minute Holding Pattern

035° 7700

215°

215° 7700

GS 3.00° TCH 55

5.5 NM

CATEGORY	A	B	C	D
S-ILS 22	6017-½ 200 (200-½)			
S-LOC 22	6140-½ 323 (400-½)			
CIRCLING	6400-1 563 (600-1)		6420-1½ 583 (600-1½)	6640-2½ 803 (900-2½)

SW-1, 03 SEP 2026 to 01 OCT 2026
SW-1, 03 SEP 2026 to 01 OCT 2026