

WAAS CH 49108 W35A	APP CRS 353°	Rwy Ldg 4605 TDZE 1823 Apt Elev 1827
--	------------------------	---


RNAV (GPS) RWY 35
CURTIS FLD (BBD)

RNP APCH - GPS.

- V** For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C.
A Baro-VNAV and YDP NA when using JCT altimeter setting. Rwy 35 helicopter visibility reduction below ¼ SM NA. When local altimeter setting not received, use JCT altimeter setting and increase LPV DA to 2190 feet; increase LNAV/VNAV DA to 2287 feet and all visibilities ⅓ SM. Increase all MDAs 120 feet and LNAV visibility Cat C ¼ SM.

MISSED APPROACH: Climb to 4000
direct OVACU and on track 263° to
VIVCU and left turn on track 150° to
BREDY and hold.

AWOS-3 118.375	HOUSTON CENTER 132.35 317.5	UNICOM 122.8 (CTAF) 0
--------------------------	---------------------------------------	---------------------------------



4000 ↑	OVACU ☼	tr 263°	VIVCU ☼	tr 150°	BREDY △	JENEV	4 NM Holding Pattern
GP 3.00° TCH 48°							
CATEGORY	A		B		C		D
LPV DA	2073-1		250 (300-1)				NA
LNAV/ VNAV	2170-1		347 (400-1)				NA
LNAV MDA	2280-1		457 (500-1)		2280-1 ³ / ₈ 457 (500-1 ³ / ₈)		NA

