

WAAS

CH 69210

W23A

APP CRS

233°

Rwy Ldg

5501

TDZE

872

Apt Elev

878

RNAV (GPS) RWY 23


LINCOLN COUNTY RGNL (IPJ)

RNP APCH.

When local altimeter setting not received, use Charlotte altimeter setting: increase LPV DA to 1212 feet, LNAV/VNAV DA to 1204 feet and all visibilities 1/8 SM; increase all MDAs 80 feet and visibility Cats C and D 1/4 SM. Baro-VNAV and VDP NA when using Charlotte altimeter setting. Rwy 23 helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C.

MISSED APPROACH:
Climb to 3200 direct IWWON and hold.

AWOS-3 119.675	CHARLOTTE APP CON 134.75 257.2	CLNC DEL (GCO) 124.9	UNICOM 123.05 (CTAF) 0
-------------------	-----------------------------------	-------------------------	---------------------------



ELEV 878

TDZE 872

3200 IWWON

* LNAV only

RW23

GATEQ 2 NM to RW23

CISBU 2500

JIVOM 3000

GP 3.00° TCH 47

1.2 NM

0.8 NM

3 NM

7.4 NM

CATEGORY	A	B	C	D
LPV DA	1149-7/8	277 (300-7/8)		
LNAV/VNAV DA	1141-7/8	269 (300-7/8)		
LNAV MDA	1280-1 408 (500-1)	1280-1 1/8 408 (500-1 1/8)		
CIRCLING	1400-1 522 (600-1)	1440-1 562 (600-1)	1660-2 1/4 782 (800-2 1/4)	1660-2 1/2 782 (800-2 1/2)

REIL Rwys 5 and 23 0

MIRL Rwy 5-23 0