

WAAS CH 93723 W01A	APP CRS 008°	Rwy Ldg 5000 TDZE 436 Apt Elev 436
--	------------------------	---

RNAV (GPS) RWY 1
FAYETTE COUNTY (FYE)



RNP APCH - GPS.	
-----------------	--

T Baro-VNAV and VDP NA when using Frederick W Smith Intl altimeter setting. Rwy 1 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C . When local altimeter setting not received, use Frederick W Smith Intl altimeter setting: increase LPV DA to 843 feet and all visibilities $\frac{1}{2}$ SM; increase LNAV/VNAV DA to 905 feet and all visibilities $\frac{1}{4}$ SM; increase all MDA 100 feet and visibility LNAV Cat C $\frac{1}{4}$ SM and Circling Cat C $\frac{1}{2}$ SM.


MISSED APPROACH:
Climb to 3000 direct
RSTEE and hold.

AWOS-3 119.875	MEMPHIS APP CON 125.8 338.3	CTAF 122.9
--------------------------	---------------------------------------	----------------------

MISSED APCH FIX




ELEV 436		TDZE 436
----------	--	----------



REF R

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 20).



CATEGORY		A	B	C	D
LPV	DA	747-1	311 (400-1)		NA
LNAV/ VNAV	DA	809-1½	373 (400-1½)		NA
LNAV	MDA	1060-1 624 (700-1)	1060-1¾ 624 (700-1¾)		NA
CIRCLING		1060-1 624 (700-1)	1160-2 724 (800-2)		NA