


WAAS CH 69536 W22A	APP CRS 218°	Rwy Ldg TDZE Apt Elev	3700 354 354
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 22
WASILLA (IYS) (PAWS)

RNP APCH. ⚠ Circling NA to Rwy 4S and 22S. Baro-VNAV and VDP NA when using Palmer altimeter setting. Rwy 22 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C. When local altimeter setting not received, use Palmer altimeter setting and increase all DA 46 feet, MDA 60 feet and all visibilities ½ mile.	MISSED APPROACH: Climb to 1000 then climbing right turn to 3000 direct BGQ VORTAC and hold.
--	---

AWOS-3P 135.25	ANCHORAGE APP CON 119.1 363.2	CTAF 122.8 0
--------------------------	---	------------------------



1000

↑

3000

↗

BGQ

⬢

ODUWU

1.9 NM to RW22

WOKNA

2500

JODBI

4400

*LNAV only

RW22

218°

1060*

*1.2 NM to RW22

2500

227°

GP 3.31°

TCH 40

1.2 NM

0.7 NM

4.1 NM

6 NM

CATEGORY	A	B	C	D
LPV DA	604-¾	250 (300-¾)	NA	
LNAV/VNAV DA	821-1½	467 (500-1½)	NA	
LNAV MDA	800-1	446 (500-1)	NA	
CIRCLING	1000-1	646 (700-1)	NA	

MIRL Rwy 4-22

REIL Rws 4 and 22