

WAAS CH 53636 W04A	APP CRS 038°	Rwy Ldg TDZE Apt Elev	3700 352 354
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 4

WASILLA (IYS) (PAWS)

RNP APCH


▼

▲

Circling NA to Rwy 4S and 22S. Baro-VNAV and VDP NA when using Palmer altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. When local altimeter setting not received, use Palmer altimeter setting and increase all DA 46 feet, all MDA 60 feet and all visibilities ¼ mile.

MISSED APPROACH: Climb to 1000 then climbing left turn to 3000 direct BGQ VORTAC and hold.

AWOS-3P 135.25	ANCHORAGE APP CON 119.1 363.2	CTAF 122.8 0
--------------------------	---	------------------------



4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).

1000

3000

BGQ

6000

2500

GP 3.00°

TCH 45

218°

038°

038°

1900

*960

1.3 NM to RW04

RW04

5 NM

3 NM

0.5 NM

1.3 NM

CATEGORY	A	B	C	D
LPV DA	602-¾	250 (300-¾)	NA	
LNAV/VNAV DA	828-1⅝	476 (500-1⅝)	NA	
LNAV MDA	780-1	428 (500-1)	NA	
CIRCLING	1000-1	646 (700-1)	NA	

ELEV 354

TDZE 352

0.4% UP

1690 X 60

0.5% UP

3700 X 75

2.2% UP

MIRL Rwy 4-22 0

REIL Rwy 4 and 22 0

AK, 03 SEP 2026 to 29 OCT 2026

AK, 03 SEP 2026 to 29 OCT 2026