

LOC I-UTA <u>110.95</u> Chan 46 (Y)	APP CRS 347°	Rwy Idg 8500 TDZE 194 Apt Elev 194
---	------------------------	---

ILS or LOC RWY 35
TUNICA MUNI (UTA)

T VDP NA with Memphis altimeter setting. When local altimeter not received, use Memphis altimeter setting and increase S-ILS 35 DA to 480 and all MDA 100 feet, increase S-LOC 35 Cats C and D and Circling Cat C visibility ¼ mile. **A** For inoperative MALSR when using Memphis altimeter setting increase S-ILS 35 all Cats visibility to 1 mile.

MALSR



MISSED APPROACH: Climb to 700 then climbing left turn to 1900 direct UJM VOR/DME and hold.

AWOS-3 118.075	MEMPHIS APP CON 119.1 291.6	CLNC DEL 118.9	UNICOM 123.0 (CTAF) 0
--------------------------	---------------------------------------	--------------------------	---------------------------------

LOCALIZER 110.95
I-UTA
Chan 46 (Y)

MEMPHIS
7.5 MEM
Chan 122

Diagram illustrating the location of the MARVELL station relative to R-351 and Chan 83 (Y). The station is located 1710 meters from R-351 at a bearing of 086° (17.5°). The station name MARVELL is highlighted in a box, with coordinates 113.65 UJM and Chan 83 (Y) indicated below it.

MSA UJM 25 NM

2100

ELEV 194	TDZE 194
----------	----------

REIL Rwy 17 **L**
HRL Rwy 17-35 **L**

FAF to MAP 5.2 NM

Knots	60	90	120	150	180
Min:Sec	5:12	3:28	2:36	2:05	1:44

700	1900	UJM
		

*LOC only.

Remain
within 10 NM

CATEGORY	A	B	C	D
S-ILS 35	394-1/2 200 (200-1/2)			
S-LOC 35	640-1/2 446 (500-1/2)		640-7/8 446 (500-7/8)	
CIRCLING	680-1 486 (500-1)	740-1 546 (600-1)	760-1 1/2 566 (600-1/2)	760-2 566 (600-2)