

WAAS CH 72834 W19A	APP CRS 191°	Rwy Ldg 5001 TDZE 221 Apt Elev 221
--	------------------------	---

RNAV (GPS) RWY 19
PANOLA COUNTY (PMU)

▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F).
▲ NA DME/DME RNP-0.3 NA. Baro-VNAV and VDP NA when using Oxford altimeter setting.
When local altimeter setting not received, use Oxford altimeter setting and increase LPV DA to 571,
LNAV/VNAV DA to 1116 and all MDA 80 feet, increase LPV all Cats visibility $\frac{3}{8}$ mile,
LNAV/VNAV all Cats visibility $\frac{1}{2}$ mile, LNAV Cat B visibility $\frac{1}{4}$ mile, LNAV Cats C, D visibility $\frac{1}{2}$ mile,
and Circling Cats B, C visibility $\frac{1}{4}$ mile. Rwy 19 helicopter visibility reduction below $\frac{3}{4}$ SM NA.

MISSED APPROACH:
Climb to 1100 then
climbing left turn to
2800 direct SUBOY
and hold.

AWOS-3PT 118.225	MEMPHIS CENTER 128.5 279.55	UNICOM 122.8 (CTAF) 0
----------------------------	---------------------------------------	---------------------------------

