

WAAS CH 70403 W20A	APP CRS 203°	Rwy Ldg TDZE Apt Elev	5499 1178 1178
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 20

WILLIAMSBURG-WHITLEY COUNTY (BYL)

RNP APCH.

Rwy 20 helicopter visibility reduction below ¾ SM NA.
For uncompensated Baro-VNAV systems,
LNAV/VNAV NA below -17°C or above 54°C.

-16°C

MISSED APPROACH: Climb
to 4900 direct ICIKO and hold,
continue climb-in-hold 4900.

AWOS-3 119.575	INDIANAPOLIS CENTER 124.625 371.925	UNICOM 122.7 (CTAF) 0
--------------------------	---	---------------------------------

The chart displays the RNAV (GPS) RWY 20 approach. Key features include:

- Initial Approach:** 30 NM to LIKCI, 10 NM to LIKCI, 4000 ft MSL.
- Hold:** 4 NM, 203° heading, 4000 ft MSL.
- IF/IAF:** LIKCI, 203° heading.
- FAF:** JUBKA, 3100 ft MSL, 203° heading.
- NUYV:** 2.8 NM to RW20, 1412± ft MSL.
- RW20:** 1178 ft MSL.
- MISSED APCH FIX:** ICIKO, 203° heading, 5 NM distance.
- GP:** 3.00° TCH 45.

ELEV 1178	TDZE 1178	4900 ICIKO VGSi and RNAV glidepath not coincident (VGSi Angle 3.17/TCH 30).			
203°		4 NM Holding Pattern			
349° x 100		*LNAV only.			
0.4% UP		NUYV 2.8 NM to RW20			
2		* 1.4 NM to RW20			
MIRL Rwy 2-20 0		JUBKA 3100			
REIL Rwy 2 and 20 0		2100*			
		3100			
		6000 4000			
		GP 3.00° TCH 45			
		1.4 1.4 3.1 NM 7 NM			
CATEGORY	A	B	C	D	
LPV DA	1651-1⅜ 473 (500-1⅜)				
LNAV/VNAV DA	1670-1⅝ 492 (500-1⅝)				
LNAV MDA	1680-1	502 (600-1)	1680-1⅝	502 (600-1⅝)	
CIRCLING	1760-1 582 (600-1)	1860-1 682 (700-1)	2240-3 1062 (1100-3)	2260-3 1082 (1100-3)	

WILLIAMSBURG, KENTUCKY

WILLIAMSBURG-WHITLEY COUNTY (BYL)

Amdt 1C 22APR21

36°48'N-84°12'W

RNAV (GPS) RWY 20