

WAAS CH 53334 W09A	APP CRS 090°	Rwy Ldg TDZE 1478 Apt Elev 1478
--	------------------------	---

RNAV (GPS) RWY 9

WAGNER MUNI (AGZ)

RNP APCH - GPS.

NA

Circling NA to Rwys 14 and 32. Baro-VNAV NA. Rwy 9 helicopter visibility reduction below ¾ SM NA. Use Yankton altimeter setting; when not received use O'Neill altimeter setting and increase all DAs 51 feet, all MDAs 60 feet and increase LPV all Cats visibility ⅛ SM, and LNAV/VNAV all Cats visibility ⅙ SM.

MISSED APPROACH: Climb to 3500 direct NEBYI and hold.

AWOS-3P 128.325	YKN AWOS-3PT 119.05	MINNEAPOLIS CENTER 128.0 257.95	AUNICOM 122.8 (CTAF) 0
---------------------------	-------------------------------	---	----------------------------------

4 NM Holding Pattern

6000 ← 270°
3400 → 090°

GP 3.00°
TCH 40

5 NM

1.9 NM

2.8 NM

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 26).

3500 NEBYI

090°

3500 X 60' 2232 X 150

0.3% UP

CATEGORY	A	B	C	D
LPV DA	1847-1	369 (400-1)	NA	
LNAV/VNAV DA	2053-1½	575 (600-1½)	NA	
LNAV MDA	2020-1	542 (600-1)	NA	
CIRCLING	2080-1	602 (700-1)	NA	

MRL Rwy 9-27 0

WAGNER, SOUTH DAKOTA

Orig-D 21MAR24

43°04'N-98°18'W

WAGNER MUNI (AGZ)

RNAV (GPS) RWY 9