



WAAS CH 69625 W31A	APP CRS 309°	Rwy Ldg TDZE 733 Apt Elev 777
--	------------------------	---

RNAV (GPS) RWY 31

ARDMORE MUNI (ADM)

RNP APCH - GPS.		MALSR 	MISSED APPROACH: Climb to 3600 direct RRDEE and hold.	
	For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Inop table does not apply to LPV all Cats. For inop ALS, increase LNAV/VNAV all Cats and LNAV Cats C and D visibility to 1 1/2 SM.			
ATIS 125.6	FORT WORTH CENTER 124.75 323.0	ARDMORE TOWER ★ 118.5 (CTAF) 0 257.7	GND CON 121.8	UNICOM 122.95



3600 ↑ RRDEE		LIBTE 2600		NIXHE 4 NM Holding Pattern	
UMEHU 1.8 NM to RW31		1.2 NM to RW31		130° → 6000 ← 310° 3600	
RW31		1340		GP 3.00° TCH 49	
1.2 NM		0.6		3.9 NM	
1.2 NM		0.6		7.5 NM	
CATEGORY	A	B	C	D	
LPV DA	933-1/2		200 (200-1/2)		
LNAV/VNAV DA	1200-1		467 (500-1)		
LNAV MDA	1160-1/2	427 (400-1/2)	1160-3/4	427 (400-3/4)	
CIRCLING	1300-1 523 (600-1)	1440-1 663 (700-1)	1500-2 723 (800-2)	1700-3 923 (1000-3)	