

INDIANAPOLIS DEP CON
124.95 317.8 (EAST)
119.05 317.8 (WEST)
D-ATIS 134.25
CLNC DEL
128.75 251.1
CPDLC
GND CON
121.9
INDY TOWER
120.9 251.1

RADAR required. DME required.

**TOP ALTITUDE:
AS ASSIGNED
BY ATC**

FORT WAYNE
117.8 FWA
Chan 125

CHAMPAIGN
115.75 CMI
Chan 104(Y)

LOCALIZER
111.75 I-UZK
Chan 54(Y)

BRICKYARD
116.3 VHP
Chan 110

I-UZK
2.6

LOCALIZER
111.15 I-OQV
Chan 48(Y)

DAYTON
114.5 DGN
Chan 92

LOCALIZER
111.15 I-FVJ
Chan 48(Y)

I-FVJ
2.3

SHELBYVILLE
116.15 SHB
Chan 108(Y)


POCKET CITY
113.3 PXV
Chan 80

R-3401B

R-3401A

R-3403B

R-3403A



TAKEOFF MINIMUMS:

Rwy 5L/R, 14, 23L/R, 32: Standard.

NOTE: Select appropriate localizer/DME frequency/channel prior to departure.

NOTE: Accelerate to 250K until reaching 10000. If unable advise ATC.

NOTE: Jet aircraft only.

(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.