

WAAS Ch 82599 W18A	APP CRS 178°	Rwy Ldg 8743 TDZE 504 Apt Elev 508
--	------------------------	---

RNAV (GPS) RWY 18R

LAREDO INTL (L.R.D)

⚠

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C (34°F) or above 54°C (130°F). Circling NA West of Rwy 14 and 36L. DME/DME RNP-0.3 NA. For inop ALS, increase LPV Cat E visibility to ¾ SM, LNAV/VNAV all Cats visibility to ⅞ SM, and LNAV Cats C/D/E to 1 SM.

MALSR

MISSED APPROACH:

Climb to 1000 then climbing left turn to 2500 direct ELKOS and hold.

ATIS 125.775	HOUSTON CENTER 127.8 307.2	LAREDO TOWER* 120.1(CTAF) 257.9	GND CON 121.8	UNICOM 122.95
------------------------	--------------------------------------	---	-------------------------	-------------------------

ELEV 508

D

TDZE 504

MIRL Rwy 14-32
HIRL Rwy 18R-36L and 18L-36R

1000	2500	ELKOS	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 50).		4 NM Holding Pattern
*LNAV only		ICANU 2.2 NM to RW18R	JINSA 2300	358°	3000
RW18R		*1 NM to RW18R	*1260	178°	2300
1NM		1.2	3.3 NM	5.8 NM	GP 3.00° TCH 57
CATEGORY	A	B	C	D	E
LPV DA	704-½ 200 (200-½)				
LNAV/VNAV DA	810-½ 306 (400-½)				
LNAV MDA	880-½ 376 (400-½)		880-⅝ 376 (400-⅝)		
CIRCLING	940-1 432 (500-1)	980-1 472 (500-1)	1100-1½ 592 (600-1½)	1200-2¼ 692 (700-2¼)	1200-2½ 692 (700-2½)

LAREDO, TEXAS

Amdt 2 01FEB18

27°33'N-99°28'W

LAREDO INTL (L.R.D)

RNAV (GPS) RWY 18R