

SEVYR THREE DEPARTURE

TOP ALTITUDE:
10000

WASATCH
.8 TCH ■■■
Chan 115

11500

DLIA
16.1 DTA
Chan 108

MILFORD
112.1 MLF

COALDALE
17.7 OAL :E:
Chgn 124

NOTE: Chart not to scale.

SW-4, 01 OCT 2026 to 29 OCT 2026

(CONTINUED ON FOLLOWING PAGE)

SALT LAKE CITY, UTAH
SALT LAKE CITY INTL (SLC)

SALT LAKE CITY DEP CON
128.1 307.05
D-ATIS
124.75 125.625
CLINC DEL
127.3 379.975
CPDLC

TAKEOFF MINIMUMS

Rwys 14, 16L/R, and 17: NA - Operational.

Rwy 32: 400-1 or standard with a minimum climb of 450' per NM to 7500.

Rwys 34L/R and 35: Aircraft assigned heading 263° CW through 322°

standard with a minimum climb of 260' per NW to 7500.

Aircraft assigned heading 323° CW through 343°

standard with a minimum climb of 340' per NM to 7500.

NOTE: This is a RADAR vector departure to assigned route or fix.

NOTE: For turbojet and turboprop aircraft only.

NOTE: RADAR required.