SUMTER, SOUTH CAROLINA

HI-TACAN Z RWY 22R

TACAN	APCH CRS		22R	22L
SSC Chan 38	222°	Rwy ldg	10,014	8014
		TDZE	240	235
		Arpt Elev	241	241

[USAF] SHAW AFB (KSSC)

RADAR required when R-6002 active.

▼ * When ALS inop, increase vis to 1½ miles.
** When ALS inop, increase vis to 1⅜ miles.

ALSF-1

MISSED APPROACH: Climbing to 2000, intercept SSC TACAN R-223 to PINIE and hold.

ATIS★	APP CON★	TOWER★	GND CON
132.125 270.1	125.4 318.1	126.65 254.25	126.1 275.8

USAF Only: When Rwy 4L VGSI inop, circling to Rwy 4L at night requires approval from MAJCOM director of Ops or equivalent. Terrain 242' MSL, 200' prior to threshold.

USAF Only: When VGSI inop, sidestep to Rwy 22L, circling to Rwy 22L at night requires approval from MAJCOM Director of Ops or equivalent. Terrain 239' MSL, 200' prior to threshold, 200' right of course.

SSC 33 R-042 042° 26.5K 222° (IAF) CHILI SSC 23 11,000 2000 222°

(c) 5.2 (a) (c) 042° 332 (b)

1400 2047 818 (IF) GABLE SSC 11 1700 672 FASNO SSC 4.9 REBIE SSC 1 652 1340 1049 854 R-6002

SHAW Chan 38 SSC

SSC 18 223° 043° PINIE SSC 11 R-223 R-215 Remain West of SSC R-215

MSA SSC 25 NM 180° 3100 090° 2400

EMERG SAFE ALT 100 NM 3800

2000 SSC R-223 PINIE SSC 11

SSC TACAN SSC 2 REBIE SSC 1 FASNO SSC 4.9 GABLE SSC 11 CHILI SSC 23 11,000 222° 2000 1700 2.95° TCH 52 0.6 NM 3.9 NM

ELEV 241 TDZE 22R 240 TDZE 22L 235

222° 22R 22L 519 502 450 392 268 TWR 340 10,014 x 150 8014 x 150 4L 4R

CATEGORY	C	D	E
S-22R*	760/55 520 (600-1)		
SIDESTEP 22L**	760/55 505 (600-1)		
CIRCLING	1000-2¼ 759 (800-2¼)	1000-2½ 759 (800-2½)	1000-2¾ 759 (800-2¾)

HIRL all rwys

SUMTER, SOUTH CAROLINA 33°58'N-80°28'W SHAW AFB (KSSC)

Amdt 1 07NOV19

HI-TACAN Z RWY 22R

SE-2, 01 OCT 2026 to 29 OCT 2026