

WAAS
CH **82614**
W35A

APP CRS
354°

Rwy Ldg **6893**
TDZE **1745**
Apt Elev **1749**

RNAV (GPS) RWY 35
WATERTOWN RGNL (ATY)

RNP APCH - GPS.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. For inop ALS, increase LNAV Cat C/D visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 3600 direct BOBDE and hold.

ASOS 126,625	MINNEAPOLIS CENTER 128.5 306.2	UNICOM 123,05 (CTAF) 0
------------------------	--	----------------------------------

MISSED APCH FIX

4 NM

BOBDE

MSA RW35 25 NM

4600

ELEV 1749 **D** TDZE 1745

REIL Rwy 12, 17 and 30

HIRL Rwy 17-35

MIRL Rwy 12-30

1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

47

48

49

50

51

52

53

54

55

56

57

58

59

60

61

62

63

64

65

66

67

68

69

70

71

72

73

74

75

76

77

78

79

80

81

82

83

84

85

86

87

88

89

90

91

92

93

94

95

96

97

98

99

100

6899 X 100

6893 X 100

354°

4 NM Holding Pattern

6000 4000

174° 354°

GP 3.00° TCH 53

5.9 NM 2.8 NM 2.4 NM 1.1 NM

3600 BOBDE

3600

CATEGORY	A	B	C	D
LPV DA	1945-½ 200 (200-½)			
LNAV/VNAV DA	2180-¾ 435 (500-¾)			
LNAV MDA	2160-½	415 (500-½)	2160-¾	415 (500-¾)
CIRCLING	2260-1	511 (600-1)	2500-2¼ 751 (800-2¼)	2500-2½ 751 (800-2½)