

ILS Z or LOC RWY 36L

LOC I-LTS 110.3	APCH CRS 355°	Rwy Ldg 13,440 TDZE 1354 Arprt Elev 1382	[USAF]	ALTUS AFB (KLTS)
---------------------------	-------------------------	---	--------	------------------

DME or RADAR required
▲ *When ALS inop, increase RVR to 40 and vis to 1/2 mile;
RVR 18 authorized with use of FD or AP or HUD to DA.
**When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CDE vis to 1 1/2 miles.

ATIS ★
109.8 273.5

FORT WORTH CENTER
133.5 350.35

APP CON
125.1 353.7

TOWER ★
119.65 254.4

GND CON
121.85 275.8

*** When ALS inop, increase RVR to 55 and vis to 1 mile.

**** Circling not authorized W of Rwy 18R-36L.

CATEGORY	A	B	C	D	E
S-ILS 36L*	1554/24				
S-LOC 36L**	1800/24	446 (500-1/2)	1800/45	446	(500-7/8)
CIRCLING****	1800-1 418 (500-1)	1840-1 458 (500-1)	1880-1 1/2 498 (500-1 1/2)	2080-2 1/4 698 (700-2 1/4)	2300-3 918 (1000-3)
SACYO FIX MINIMUMS					
S-LOC 36L***	1680/24	326 (300-1/2)	1680/26	326	(300-1/2)
CIRCLING****	1780-1 398 (400-1)	1840-1 458 (500-1)	1880-1 1/2 498 (500-1 1/2)	2080-2 1/4 698 (700-2 1/4)	2300-3 918 (1000-3)