

WAAS CH 97518 W25A	APP CRS 256°	Rwy Ldg 6248 TDZE 5507 Apt Elev 5507
--	------------------------	---

RNAV (GPS) RWY 25

FOUR CORNERS RGNL (FMN)

RNP APCH-GPS.

V Baro-VNAV and VDP NA when using Durango altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. Circling NA for Cat D southeast of Rwy 5 and south of Rwy 25. When local altimeter setting not received, use Durango altimeter setting and increase LPV DA to 5950 feet and all visibilities ½ SM. Increase LNAV/VNAV DA to 6312 feet and all visibilities ½ SM. Increase all MDAs 260 feet and LNAV visibilities Cat C/D ¾ SM, and Circling visibility Cat B ¼ SM and Cat C ½ SM.

MISSED APPROACH: Climb to 8000 direct HASIT and hold.

ATIS
127.15


DENVER CENTER
118,575 348.7

FARMINGTON TOWER★
118.9 (CTAF) **L** 257.8

GND CON
121.7

UNICOM
122.95

MISSED APCH FIX



 DURANGO
DRO

9900
170°
(23.2)

Aztec
Muni

MSA RW 25 25 NM

9700

ELEV 5507	D	TDZE 5507
-----------	----------	-----------

D

TDZE 5507

8000	HASIT
	

8000 HASIT

KODYD
3.4 NM to
RW25

EPOTE
7800

POMEE
8400

1.9 NM to
RW25

RW25

6640

25°

7800

GP 3.00°
TCH 50

GP 3.00°
TCH 56

CATEGORY		A	B	C	D
LPV	DA	5707-3 $\frac{3}{4}$		200 (200-3 $\frac{3}{4}$)	
LNAV/ VNAV	DA	6069-1 $\frac{5}{8}$		562 (600-1 $\frac{5}{8}$)	
LNAV	MDA	5880-1		373 (400-1)	
CIRCLING		6020-1	6140-1	6380-2 $\frac{1}{2}$	6400-3
		513 (600-1)	633 (700-1)	873 (900-2 $\frac{1}{2}$)	893 (900-3)

REIL Rwy 23 and 25 **L**
MIRL Rwy 5-23 and 7-25 **L**

FARMINGTON, NEW MEXICO

Amdt 2 02DEC21

36°44'N-108°14'W

FOUR CORNERS RGNL (FMN)

RNAV (GPS) RWY 25