


WAAS CH 49005 W12A	APP CRS 123°	Rwy Ldg TDZE 548 Apt Elev 549
--	------------------------	---

RNAV (GPS) RWY 12

JEFFERSON CITY MEML (JEF)

RNP APCH - GPS.	MISSED APPROACH: Climb to 2800 direct FATPI and hold.
For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 48°C. Rwy 12 helicopter visibility reduction below ¾ SM NA. Circling Rwy 9 NA at night.	

ASOS 133.625	MIZZU APP CON 124.375 353.925	JEFFERSON CITY TOWER ★ 125.6 (CTAF) 0	GND CON 121.7	UNICOM 122.95
------------------------	---	---	-------------------------	-------------------------



ELEV 549		TDZE 548	
4 NM Holding Pattern		2800 ↑ FATPI	
6000 ← 303° 3000 → 123°		1.5 NM to RW12	
GP 3.50° TCH 45		RW12	
6.5 NM		3.4 NM	
CATEGORY	A	B	C
LPV DA	874-1 326 (400-1)		
LNAV/VNAV DA	964-1½ 416 (500-1½)		
LNAV MDA	1160-1 612 (700-1)	1160-1¾ 612 (700-1¾)	
CIRCLING	1240-1 691 (700-1)	1320-2¼ 771 (800-2¼)	1560-3 1011 (1100-3)

REIL Rwys 9, 12, and 27

MIRL Rwy 9-27

HIRL Rwy 12-30