

WAAS CH 82025 W01A	APP CRS 015°	Rwy Ldg 6400 TDZE 82 Apt Elev 82
--	------------------------	---


RNAV (GPS) Z RWY 1
DILLINGHAM (DLG)(PADL)

RNP APCH - GPS.

▼ Circling NA east of Rwy 1-19. For uncompensated Baro-VNAV systems, procedure NA below -20°C or above 54°C. Rwy 1 helicopter visibility reduction below $\frac{3}{4}$ SM. NA. Baro-VNAV and VDP NA when using Manokotak altimeter setting. When local altimeter setting not received, use Manokotak altimeter setting and increase LPV DA to 367 feet; increase LNAV/VNAV DA to 486 feet and all visibilities $\frac{1}{8}$ SM. Increase all MDAs 40 feet and LNAV visibility Cat/C $\frac{1}{2}$ SM.

MISSED APPROACH: Climb to 600 then climbing right turn to 2000 direct UVHAL and hold.

AFIS 125.0	ANCHORAGE CENTER 132.75 282.35	DILLINGHAM RADIO 123.6 (CTAF) 0
----------------------	--	---



4 NM Holding Pattern 6000 ← 195° 2000 → 015° GP 3.00° TCH 45		FISAX		SUBWA 1700 1.4 NM to RW01 RW01		600 2000 UVHAL △
		7.5 NM		3.5 NM		1.4 NM
CATEGORY	A	B	C	D		
LPV DA	332-1 250 (300-1)					
LNAV/VNAV DA	451-1 369 (400-1)					
LNAV MDA	580-1 498 (500-1)			580-1 $\frac{3}{8}$ 498 (500-1 $\frac{3}{8}$)		
CIRCLING	580-1 498 (500-1)			700-1 $\frac{3}{4}$ 618 (700-1 $\frac{3}{4}$)		700-2 618 (700-2)

