

WAAS
CH **78113**
W23A

APP CRS
227°

Rwy Ldg
TDZE
Apt Elev

6002
1201
1201

AL-5369 (FAA)

RNAV (GPS) RWY 23

SHENANDOAH VALLEY RGNL (SHD)

RNP APCH - GPS.


Baro-VNAV NA when using Charlottesville altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. Visibility reduction by helicopters NA. When local altimeter setting not received, use Charlottesville altimeter setting and increase all DA 130 feet and all MDA 140 feet. Increase LPV and LNAV/VNAV all Cats visibility ¼ SM, LNAV Cat C visibility ¼ SM, LNAV Cat D ½ SM, Circling Cat C ½ SM and Cat D ¼ SM.

MISSED APPROACH:
Climb to 5300 direct GABEL and hold, continue climb-in-hold to 5300.

AWOS-3
124.925

POTOMAC APP CON
132.85 323.125

UNICOM
123.0 (CTAF) 0



ELEV 1201

D

TDZE 1201

3300

5300

GABEL

*LNAV only

DORDE 3 NM to RW23

FLLAT

ELOPY

ADIOS

5 NM Holding Pattern

047°

227°

4800

GP 3.00° TCH 45

3 NM

5.2 NM

2.9 NM

3.2 NM

CATEGORY	A	B	C	D
LPV DA		1451-¾	250 (300-¾)	
LNAV/VNAV DA		1530-1	329 (400-1)	
LNAV MDA		1580-1	379 (400-1)	
CIRCLING	1660-1 459 (500-1)	1760-1 559 (600-1)	1900-2 699 (700-2)	2060-2¾ 859 (900-2¾)

REIL Rwy 23 0

HIRL Rwy 5-23 0