

WAAS CH 93732 W32A	APP CRS 322°	Rwy Ldg TDZE 1130 Apt Elev 1136
--	------------------------	---

RNAV (GPS) RWY 32


MORRIS MUNI/CHARLIE SCHMIDT FLD (MOX)

RNP APCH - GPS.

Baro-VNAV and VDP NA when using BBB altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use BBB altimeter setting and increase LPV DA to 1380 feet and LNAV/VNAV DA to 1477 feet. Increase all MDAs 60 feet and visibility LNAV Cat C ½ SM and visibility Circling Cat C ¼ SM.

MISSED APPROACH: Climb to 3000 direct ZITOG and hold.

AWOS-3PT 118.6	MINNEAPOLIS CENTER 126.1 269.2	UNICOM 122.8 (CTAF) 0
--------------------------	--	---------------------------------



3000

↑

ZITOG

✦

1 NM to RW32

↓

2100

✖

3000

✖

1 NM

2 NM

2.8 NM

7.8 NM

EXJUP

4 NM Holding Pattern

142° → 6000

← 322° 3500

GP 3.00°

TCH 40

CATEGORY	A	B	C	D
LPV DA	1330-1	200 (200-1)		NA
LNAV/VNAV DA	1419-1	289 (300-1)		NA
LNAV MDA	1480-1	350 (400-1)		NA
CIRCLING	1560-1 424 (500-1)	1600-1 464 (500-1)	1860-2 724 (800-2)	NA

HIRL Rwy 14-32

REIL Rwy 14 and 32

NC-1, 01 OCT 2026 to 29 OCT 2026

NC-1, 01 OCT 2026 to 29 OCT 2026