


APP CRS	Rwy Ldg	4126
237°	TDZE	850
	Apt Elev	851

RNAV (GPS) RWY 23

BLUFFTON (5G7)

RNP APCH.	Use Findlay altimeter setting; when not received use Lima altimeter setting and increase all MDA 20 feet and Circling Cat D visibility ¼ SM.		MISSED APPROACH: Climbing right turn to 2500 direct FBC VORTAC and hold.
▼ ▲ NA			
FDY ASOS	TOLEDO APP CON	UNICOM	
132.85	120.8 317.55	122.8 (CTAF) 0	



2500

FBC

ALPEW

2300

RW23

4.4 NM

6.2 NM

4 NM Holding Pattern

057° 6000

237° 2400

CATEGORY	A	B	C	D
LNVA MDA	1340-1	490 (500-1)	1340-1⅜ 490 (500-1⅜)	1340-1½ 490 (500-1½)
CIRCLING	1360-1 509 (600-1)	1520-1 669 (700-1)	1520-1¾ 669 (700-1¾)	1520-2 669 (700-2)

ELEV 851

TDZE 850

237°

4126 K 75

REIL Rwy 5 and 23 0

MIRL Rwy 5-23 0

EC-2, 01 OCT 2026 to 29 OCT 2026

EC-2, 01 OCT 2026 to 29 OCT 2026