

WAAS CH 86618 W13A	APP CRS 134°	Rwy Idg 6000 TDZE 130 Apt Elev 130
--	------------------------	---



RNAV (GPS) RWY 13

KLEBERG COUNTY (IKG)

T For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C (5°F) or above 48°C (118°F). DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA. **A** NA When local altimeter setting not received, use Alice altimeter setting and increase all DA 33 feet and all MDA 40 feet and LPV all Cats, LNAV/VNAV all Cats, and LNAV Cat D visibility ¼ mile. Baro-VNAV and VDP NA when using Alice altimeter setting.

MISSED APPROACH: Climb to 2000 direct OREAN and hold.

AWOS-3P 119.075	KINGSVILLE APP CON ★ 119.9 290.45	UNICOM 122.7 (CTAF) 1
---------------------------	---	--



4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 39°).

IHPOP

JOYRY 1500

ZUNIK 1.7 NM to RWY13

*LNAV only

GP 3.00° TCH 42

RWY13

6 NM

2.4 NM

0.8

0.9

CATEGORY	A	B	C	D
LPV DA		380- ³ / ₄	250 (300- ³ / ₄)	
LNAV/VNAV DA		444-1	314 (400-1)	
LNAV MDA		440-1	310 (400-1)	
CIRCLING	500-1 370 (400-1)	580-1 450 (500-1)	580-1½ 450 (500-1½)	680-2 550 (600-2)